



SSR140C-8 SINGLE DRUM ROLLER



Extended life time

- ◆ The use of water wheel type lubrication on the vibratory bearing extends the bearing life up to 5,000 hours.
- ◆ Double filtration of engine high intake air, the hydraulic system contains three stage filtration.

High efficiency

- ◆ 10% greater excitation force than other products in the same category resulting in 16.7% greater production.

Operator comfort

- ◆ Cab mounted on vibration damping mounts
- ◆ Cab temperature control
- ◆ Operator control forces have been reduced

Safety features

- ◆ Rounded bumpers front and rear
- ◆ Large rear glass and sloped hood for greater visibility

Technical specifications


Model		SSR140C-8
Load	Operating mass (kg)	14000
	Mass allocated to vibrating drum (kg)	8000
	Mass allocated to driving axle (kg)	6000
	Static linear load of vibrating drum (N/cm)	375
Compaction	Vibration frequency (Hz)	33/36
	Nominal amplitude (mm)	1.9/1.0
	Centrifugal force (kN)	290/200
	Diameter of vibrating drum (mm)	1500
	Width of vibrating drum (mm)	2130
	Vibrating drum rim thickness (mm)	25
Maneuverability	Travel speed (km/h)	0~4.6
		0~8.2
	Theoretical gradeability	50%
	Min. ground clearance (mm)	410
	Wheelbase (mm)	2980
	Steering angle (°)	± 35
	Swing angle (°)	± 12
	Min. turning outer diameter (mm)	11800
	Tire specification	20.5-25-16PR
Engine	Brand	DONGFENG CUMMINS
	Model	6BTAA5.9-C180
	Emission	/
	Rated power (kW)	132
Capacities	Battery (V × Ah)	24 × 120
	Fuel tank (L)	300
	Hydraulic oil tank (L)	150

Standard configurations

Config.	Systems	Description	Qty	Details	Remarks
Standard confi.	Main machine	SSR140C-8 single drum roller, standard	1	1. Engine 2. Travel pump 3. Vibration pump 4. Travel motor 5. Vibration motor 6. Reduction gears 7. Operating platform 8. Vibratory drum (Smooth)	9. Electrical system 10. Operating system 11. Front frame 12. Rear frame 13. Covering part 14. Rear axle assembly 15. Center articulated frame 16. Cab+Air Con
	Shed	Shed	1	Low cost	Optional
Optional confi.	Vibratory drum with welded pad foot	Drum with welded pad foot	1	Vibratory drum with welded pad foot, which cannot be removed, suitable for compaction of clay, semi-clay, rocks, gravels, expansive soil, and coal cinder base	Substitute smooth drums permissible
	Vibratory drum with assembled pad foot	Drum with assembled pad foot	1	Vibratory drum with assembled pad foot, which can be removed to form a smooth drum; suitable for compaction of clay, semi-clay, rocks, gravels, expansive soil, and coal cinder base	Optional

Dimensions

Size code	SSR140C-10
A(mm)	2980
W(mm)	2286
L(mm)	5800
D(mm)	1500
H(mm)	3200
B(mm)	2130
K(mm)	410



SANY HEAVY INDUSTRY CO. LTD.

SANY Industrial Park, Economic and Technological Development Zone, Changsha, Hunan, China, 410100
 Sales Hotline
 Tel: 0086-731-85835199
 Mail: sales@sanyglobal.com

Service Hotline
 Tel: 0086-4006098318
 Mail: CRD@sany.com.cn

The product configuration (including technical parameters) is subject to change and the delivered actual machine without notice.

www.sanyglobal.com