



SPR200C-8 PNEUMATIC TYRE ROLLER



Exceptional compaction performance

- ◆ Meeting the demands of compaction for asphalt road and cement stabilized base

Hydraulic drive system

- ◆ Continuously variable drive system provides smooth starting and stopping
- ◆ Controls are easy to learn and easy to operate

Automatic oil-spraying technology

- ◆ Pneumatic powered automatic oil-spraying prevents asphalt from sticking to the tires
- ◆ Two minute suction refill of oil tank eliminates the manual refilling
- ◆ Eliminates the safety hazard of manually applying oil

Automatic inflation system

- ◆ Tire pressure is adjustable from within the cab
- ◆ Even and consistent air pressure ensures compaction quality

Hydraulic brake system

- ◆ Hydraulic braking is engaged upon engine or transmission failure
- ◆ Braking distance is 50% less than similar equipment
- ◆ Transaxle brake is applied when the equipment stops without the need for hand brake

- ◆ Air pressure is maintained even when a tire has a slow leak

Technical specifications


	Model	SPR200C-8
Compaction	Max. operating weight (kg)	20000
	Min. operating weight (kg)	10000
	Ground pressure (kPa)	200~480
	Single tire load (t)	2.5
	Tire Inflation pressure (kPa)	200~800
	Compaction width (mm)	2085
	Overlap (mm)	36
Maneuver ability	Travel speed (km/h)	0~7.6
		0~14
	Steering angle (°)	30
	Gradeability	25%
	Swing distance (mm)	50
	Ground clearance (mm)	350
	Wheelbase (mm)	3750
	Min. turning outside diameter (mm)	17000
Engine	Brand	DONGFENG CUMMINS
	Model	4BTAA3.9-C125
	Emission	/
	Power (kW)	93
Capacities	Accumulator (V × Ah)	24 × 120
	Water tank (L)	500
	Fuel tank (L)	160
	Hydraulic oil tank (L)	100

Standard & optional configurations

Config.	Systems	Description	Qty	Details	Remarks
Standard confi.	Main machine	SPR200C-8 pneumatic roller, standard	1	1.Engine 2.Travel pump 3.Travel motor 4.Transaxle 5.Conopy 6. Front covering part	7. Front wheel assembly 8. Rear wheel assembly 9. Electrical system 10.Frame assembly 11. Water spraying system
	Cab	Cab	1	Work in windy, sandy, and extreme temperature conditions	
	Auto-oil-spraying system	Auto-oil-spraying system	1	High-grade road works	
	Centralized inflation	Centralized inflation	1	High-grade road works	
Optional config.	Rear vision system	Rear vision system	1	Work in confined areas such as residential areas	
					Optional

Dimensions

Size code	SPR200C-8
A (mm)	3750
B (mm)	2085
H (mm)	3275
K (mm)	360
L (mm)	5000
W (mm)	2036



SANY HEAVY INDUSTRY CO. LTD.

SANY Industrial Park, Economic and Technological Development Zone, Changsha, Hunan, China, 410100
 Sales Hotline
 Tel: 0086-731-85835199
 Mail: sales@sanyglobal.com

Service Hotline
 Tel: 0086-4006098318
 Mail: CRD@sany.com.cn

The product configuration (including technical parameters) is subject to change and the delivered actual machine without notice.

www.sanyglobal.com